

# HONDEX®

Digital Echo Sounder  
HE-7300-Di  
HE-1500-Di

## Next Evolution of Commercial Fishing

High-Standard Echo Sounder  
Optimized Image Presentation for Different Water Depth



Digital Echo Sounder

# HE-7300-Di

10.4"  
model

# HE-1500-Di

15"  
model

Variable Frequency Model

FROM 1KW UP TO 5KW

\* 1KW: 50/200KHZ ONLY

OUTPUT  
POWER

FROM 28KHZ UP TO 200KHZ

FREQ.

**Di** HONDEX  
DIGITAL  
TECHNOLOGY



"Di" series utilizing HONDEX's latest digital technology.



Introducing new technology of direct digital conversion. The optimized filtering even for weak signal is now available. "Deeper detection for deep water" and "Higher resolution image for shallow water" are in your hands.

### "Di" Features

- Dual display for same frequency:** Different gain settings are possible for single frequency image by splitting the image of single frequency to two different screens.
- Whole Display Gain Adjustment:** Gain adjustment reflects to whole the past image (all display presentation).
- Variable Frequency:** Applicable for variety of transducers.

## Digital Echo Sounder

# HE-7300-Di / HE-1500-Di

### Specifications

Display	10.4" Color TFT LCD (7300-Di) / 15" Color TFT LCD (1500-Di)
Number of Pixel	640 X 480
Operating Voltage	11-35V DC
Power Consumption	24W (7300-Di) / 36W (1500-Di)
Display Style	Portrait, Landscape & Reverse
Weight	Approx. 4kg (7300-Di) / Approx. 7kg (1500-Di)
Waterproof	IPX4
Output Power	1 to 5kW (Depending on the transducer)
Frequency	Dual frequency from 28, 32, 36, 40, 50, 65, 75, 100, 200kHz To use other freq., please ask your dealer.
Depth Range	5 to 2,000 Meters / Fathoms / Brazas 15 to 6,000 Feet
Max Shift Range	2,000 to 4,000 Meters / Fathoms / Brazas 6,000 to 8,000 Feet
Auto Range / Auto Shift	OFF / Range / Shift
Auto Gain	OFF / Low / High
A-Mode	OFF / ON
Fish Alarm	OFF / Small / Large
Water Temp. Alarm	OFF / In Range / Out Range (Optional water temp. sensor required)
Depth Alarm	OFF / In Range / Out Range
Expansion Mode	OFF / BL / Auto / Manual
Expansion Rate	X2, X4, X8
Background Color	4 Colors
Color Configuration	5 Patterns
Depth Unit	Meters / Feet / Fathoms / Brazas
Depth Readout	S / M / L
Scale Line	OFF / ON
Super Range	OFF / ON
Clean Echo	OFF / L / M / H
STC	L / M / H
TX Power	OFF / Low / High
NMEA Output	Depth (DBT sentence) Water Temp. (MTW sentence)

### In the Box

- Main Unit ● Power Supply Cable (DC07)



### Optional Accessories

- Thru-hull Water Temp. Sensor : TC02CS (8P-15m) + TCK01
- Transom Water Temp. Sensor : TC03-05 (8P-5m)
- Transom Water Temp. Sensor : TC03-10 (8P-10m)
- Front Cover : CV02



TC02CS



TCK01



TC03-05



CV02


### Compatible Transducer

Depth Range Unit: Meters **0-500** **0-1500** **0-2000**

Output Power	40/75	50	200	50&200	32/40	36/65	28	28/55/100
1kW				TD47(T)				
1.5kW	TD51	TD30	TD33	TD66				
1.8kW				TD67(T)				
2kW				TD68				
2.5kW	TD73				TD70			
3kW	TD83	TD113	TD89		TD80	TD81	TD88	TD87
5kW	TD93					TD95	TD98	TD97


### Dimension (HE-7300-Di)

Unit: mm



### Dimension (HE-1500-Di)

Unit: mm



Specifications are subject to change without notice.

● Dealer



**HONDEX®** is trade name of  
HONDA ELECTRONICS CO.,LTD.

20 Oyamazuka, Oiwacho,  
Toyohashi, Aichi, Japan 441-3193

TEL: 81-532-41-2512

FAX: 81-532-41-4441

HONDEX English Site

[www.honda-el.co.jp/en/marine/](http://www.honda-el.co.jp/en/marine/)

